6585 CEDAR LANE COLUMBIA, MD 21044 OFFICE. 410.531.6051

HTTP://WWW.ITGLOBALSYSTEMS.COM/

INFO@ITGLOBALSYSTEMS.COM



Technical specifications **VFLEXTOR®** 1 □ □ 8.3

Virtual, Flexible, Execution and Storage environment

vFleXtor[®] **1008.3** is a **2 node** integrated hardware/software and services appliance, which leverages processing power and robust storage, in a dense datacenter layout. The product delivers a self-sufficient, highly available and redundant computing environment which maximizes the storage and computing of a 8U form factor by offering rack mountable solution.

Hardware specifications

vFleXtor	1008.3
Chassis size	8U (2 nodes x 4U)High density 4U storage optimized chassis per node
Storage Capacity	 Up to 48 hot-swappable 3.5" SAS / SATA drive bays for shared storage (2x24 mirrored)
CPU	 2x Quad-Core Intel® Xeon® Processor 5500 with QPI up to 6.4 GT/s
Motherboard	• supports for max. motherboard size - 16" x 14.3"
RAID supported	• RAID 0, 1, 10, 0+1, 5, 6, 50, 60 supported
RAM	 Up to 12 DDR2 DIMMs per node Up to 48 GB 1333 / 1066 / 800MHz DDR3 ECC Registered memory
Expansion slots	 7x full height, full length PCI expansion slots per node
Connectivity	 Integrated dual port Gigabit Ethernet adapters VMDq support for better performance of virtualization Integrated IPMI and KVM with dedicated LAN
Power	 1200W high-efficiency (1+1) redundant power supply (per node) with PMBus PFC - Gold Level 93% Maximum Efficiency %) with PMBus Power Switch, Reset Switch & 6 LED Indicators Input -100 - 140V, 50 - 60Hz, 8 - 11.5 Amp (per node) Power Supply Safety – UL/CUL listed, TUV Certified, EN 60950/IEC 60950-Compliant, CB Report, CCC Certification
Cooling	 100% Cooling Redundancy with Adjustable Air Shroud 3x 5000 RPM Hot-swap Cooling PWM Fans (per node) 2x 5000 RPM Hot-swap Rear Exhaust PWM Fans (per node) Only High Quality Components and Fans are used for Maximum Reliability
Dimensions (per node)	 Height 7" (178mm) Depth 26" (660mm) Width 17.2" (437mm) Gross Weight 91 lbs (41.3kg)
Optional components	Slim DVD-ROM Drive

vFleXtor[®] **1008.3** is a future proof scalable iSCSI storage and computing capacity model, it is energy-efficient solution ideal for space-constrained, mission-critical deployments.

iSCSI's advantages are that it runs over ubiquitous Ethernet networks and switches, can communicate over wide area as well as local area networks, and, because it runs on top of IP, it is an extremely flexible routed protocol that facilitates virtualization. IT Global Systems has invested in a broad range of iSCSI and computing solutions ranging from the entry-level vFleXtor 500 series to the powerful vFleXtor 1000 series and the massively scalable vFleXtor 2000 series products.



According to Forrester¹, there are both hard economic benefits as well as soft benefits in adopting iSCSI storage.

"Given the hardware acquisition cost benefits as well as synergies in network staff and infrastructure, significant benefits can be gained from the use of iSCSI-based SAN architectures." Among the soft benefits is "more virtualization within the protocol. iSCSI is inherently more virtualized than Fibre Channel... allowing for more granular addressing, especially important for virtual server environments." (Forrester Research, Inc., February 2008, "Cost Comparison of iSCSI Versus Fibre Channel SAN Components")

The applications require not only the inherent ease of use and accessibility of the iSCSI protocol, but the intelligent automation and dynamic virtualization such as those in the vFleXtor architecture. While we can build your virtual infrastructure based on the vFleXtor[®] computing and storage resources, vFleXtor® still can be easily integrated within already existing computing environments.

Features

Value added services	Shared storage and computing
	 High availability Storage and computing redundancy - if one node fails or is under maintenance, all the data is still accessible on the second node Encryption
Integration	Easy to integrate and use in already existing computing environments using iSCSI Secretary computing recovered integration to any VM years ESX4.0.
	 Seamless computing resources integration to any VMware ESX4.0 environment with ability the vFleXtor[®]'s vSphere console to manage existing VMware ESX3.5 nodes
Mirroring and Redundancy	 Up to 48TB fully redundant mirrored storage, based on a distributed redundancy
Connectivity	 High-performing network shared storage using standard iSCSI protocol and accessible by multiple types of clients
Access	 Client access to the storage is implemented with multi-pathing using a minimum of two independent entry routes each over redundant physical network links.
Support	 Basic: Email with up to 1 business day response Silver: Mon-Fri, 9-5, up to 4 hours response time Gold: 24/7/365
	Platinum: Gold level + Assigned account support person with direct contact

IT Global Systems offers services to help your organization to precisely identify the computing and storage resources allocation and to ensure maximum utilization and efficiency. We will work with you – the customer – to design, configure and implement an end-to-end integrated solution matching your needs – whether for a small business, mid size or large enterprise environment.

vFleXtor can reduce complexity and lower costs, transforming IT infrastructures into more agile operations that can bring strategic advantages to the enterprise. Storage virtualization is a proven way to improve flexibility, resiliency and system performance – all while also boosting storage utilization.

Product home: http://www.vflextor.com or http://www.itglobalsystems.com/



¹ http://www.forrester.com/Research/Document/Excerpt/0,7211,43397,00.html

_